



BICO Drilling Tools, Inc. Build Rate Prediction: Ø4¾ Lambda P50 XL Adjustable												
Slick					Stabilized 1/8" Undergage				Stabilized 1/4" Undergage			
Hole Size					Hole Size				Hole Size			
ABH (°)	Ø6"	Ø6-1/4"	Ø6-1/2"	Ø6-3/4"	Ø6"	Ø6-1/4"	Ø6-1/2"	Ø6-3/4"	Ø6"	Ø6-1/4"	Ø6-1/2"	Ø6-3/4"
0.39	-	-	-	-	2.4	2.6	2.8	3.0	1.5	1.7	1.9	2.1
0.78	3.6	2.8	2.1	-	4.9	5.1	5.3	5.5	4.0	4.2	4.4	4.6
1.15	6.3	5.6	4.9	4.1	7.3	7.5	7.7	7.9	6.4	6.6	6.8	6.9
1.50	9.0	8.2	7.5	6.8	9.6	9.8	9.9	10.1	8.6	8.8	9.0	9.2
1.83	11.4	10.7	10.0	9.2	-	11.9	12.1	12.2	10.8	10.9	11.1	11.3
2.12	-	12.9	12.1	11.4	-	-	13.9	14.1	-	12.8	13.0	13.2
2.38	-	-	14.1	13.3	-	-	-	15.8	-	-	14.7	14.8
2.60	-	-	15.7	15.0	-	-	-	-	-	-	-	16.3
2.77	-	-	-	16.3	-	-	-	-	-	-	-	17.4
2.90	-	-	-	17.2	-	-	-	-	-	-	-	18.2
2.97	-	-	-	17.8	-	-	-	-	-	-	-	18.6
3.00	-	-	-	18.0	-	-	-	-	-	-	-	18.8

Predicted Build Rate figures are in °/100' and are based on theoretical calculations of a non-flexing motor. Includes Float Bore Top-Sub