



<b>BICO Drilling Tools, Inc. Build Rate Prediction: Ø6¼ Omega Adjustable with Ø6¼ P100 XL</b>									
	<b>Slick</b>			<b>Stabilized 1/8" Undergage</b>			<b>Stabilized 1/4" Undergage</b>		
	<b>Hole Size</b>			<b>Hole Size</b>			<b>Hole Size</b>		
<b>ABH (°)</b>	<b>Ø7-7/8"</b>	<b>Ø8-1/2"</b>	<b>Ø8-3/4"</b>	<b>Ø7-7/8"</b>	<b>Ø8-1/2"</b>	<b>Ø8-3/4"</b>	<b>Ø7-7/8"</b>	<b>Ø8-1/2"</b>	<b>Ø8-3/4"</b>
<b>0.39</b>	-	-	-	2.7	3.2	3.4	2.0	2.4	2.6
<b>0.78</b>	2.2	-	-	5.1	5.6	5.8	4.4	4.8	5.0
<b>1.15</b>	4.9	3.4	2.8	7.4	7.8	8.0	6.6	7.1	7.3
<b>1.50</b>	7.5	6.0	5.4	9.5	10.0	10.2	8.8	9.2	9.4
<b>1.83</b>	9.9	8.4	7.8	11.6	12.0	12.2	10.8	11.3	11.4
<b>2.12</b>	12.0	10.5	9.9	13.3	13.8	14.0	12.6	13.0	13.2
<b>2.38</b>	13.9	12.5	11.9	14.9	15.4	15.6	14.2	14.6	14.8
<b>2.60</b>	15.6	14.1	13.5	-	16.7	16.9	15.5	16.0	16.1
<b>2.77</b>	-	15.3	14.7	-	17.8	17.9	-	17.0	17.2
<b>2.90</b>	-	16.3	15.7	-	18.6	18.7	-	17.8	18.0
<b>2.97</b>	-	16.8	16.2	-	19.0	19.2	-	18.2	18.4
<b>3.00</b>	-	17.0	16.4	-	19.2	19.4	-	18.4	18.6

Predicted Build Rate figures are in %/100' and are theoretical calculations based on a non-flexing motor.