



<b>BICO Drilling Tools, Inc. Build Rate Prediction: Ø6¾ Omega SS100 SR Adjustable</b>												
<b>Slick</b>					<b>Stabilized 1/8" Undergage</b>				<b>Stabilized 1/4" Undergage</b>			
<b>Hole Size</b>					<b>Hole Size</b>				<b>Hole Size</b>			
<b>ABH (°)</b>	<b>Ø7-7/8"</b>	<b>Ø8-1/2"</b>	<b>Ø8-3/4"</b>	<b>Ø9-7/8"</b>	<b>Ø7-7/8"</b>	<b>Ø8-1/2"</b>	<b>Ø8-3/4"</b>	<b>Ø9-7/8"</b>	<b>Ø7-7/8"</b>	<b>Ø8-1/2"</b>	<b>Ø8-3/4"</b>	<b>Ø9-7/8"</b>
<b>0.39</b>	-	-	-	-	2.6	3.4	3.7	5.1	1.5	2.3	2.6	3.9
<b>0.78</b>	8.5	6.9	6.2	3.2	5.2	6.0	6.3	7.6	4.1	4.9	5.2	6.5
<b>1.15</b>	12.0	10.4	9.7	6.7	7.7	8.4	8.7	10.1	6.6	7.3	7.6	9.0
<b>1.50</b>	15.3	13.7	13.0	10.0	10.0	10.8	11.1	12.4	8.9	9.6	9.9	11.3
<b>1.83</b>	18.4	16.8	16.1	13.1	12.2	12.9	13.2	14.6	11.1	11.8	12.1	13.5
<b>2.12</b>	21.2	19.5	18.8	15.8	14.1	14.9	15.2	16.5	13.0	13.8	14.1	15.4
<b>2.38</b>	-	22.0	21.3	18.3	15.8	16.6	16.9	18.2	14.7	15.5	15.8	17.1
<b>2.60</b>	-	24.0	23.4	20.4	17.3	18.1	18.4	19.7	16.2	16.9	17.2	18.6
<b>2.77</b>	-	25.6	25.0	22.0	18.4	19.2	19.5	20.8	17.3	18.1	18.4	19.7
<b>2.90</b>	-	26.9	26.2	23.2	19.3	20.0	20.3	21.7	18.2	18.9	19.2	20.6
<b>2.97</b>	-	27.5	26.9	23.9	19.8	20.5	20.8	22.2	18.6	19.4	19.7	21.0
<b>3.00</b>	-	27.8	27.1	24.1	20.0	20.7	21.0	22.4	18.8	19.6	19.9	21.2

Predicted Build Rate Figures are in °/100' and are based on theoretical calculations of a non-flexing motor.