



<b>BICO Drilling Tools, Inc. Build Rate Prediction: Ø9-5/8" Omega x Ø8" Omega P100 XL Adjustable</b>									
<b>Slick</b>			<b>Stabilized 1/8" Undergage</b>			<b>Stabilized 1/4" Undergage</b>			
<b>Hole Size</b>			<b>Hole Size</b>			<b>Hole Size</b>			
<b>ABH (°)</b>	<b>Ø12¼"</b>	<b>Ø14¾"</b>	<b>Ø17½"</b>	<b>Ø12¼"</b>	<b>Ø14¾"</b>	<b>Ø17½"</b>	<b>Ø12¼"</b>	<b>Ø14¾"</b>	<b>Ø17½"</b>
<b>0.39</b>	-	-	-	4.0	5.5	7.3	3.5	5.0	6.8
<b>0.78</b>	5.8	2.2	-	5.9	7.4	9.2	5.4	6.9	8.7
<b>1.15</b>	8.3	4.7	-	7.8	9.3	11.1	7.3	8.8	10.6
<b>1.50</b>	10.6	7.0	2.7	9.5	11.0	12.8	9.0	10.5	12.3
<b>1.83</b>	12.8	9.2	4.9	11.2	12.7	14.5	10.7	12.2	14.0
<b>2.12</b>	14.8	11.2	6.8	12.7	14.2	16.0	12.1	13.6	15.4
<b>2.38</b>	16.5	12.9	8.6	14.0	15.5	17.3	13.4	14.9	16.7
<b>2.60</b>	18.0	14.4	10.0	15.1	16.6	18.4	14.5	16.0	17.8
<b>2.77</b>	19.1	15.5	11.2	15.9	17.4	19.2	15.4	16.9	18.7
<b>2.90</b>	20.0	16.4	12.0	16.6	18.1	19.9	16.0	17.5	19.3
<b>2.97</b>	20.4	16.8	12.5	16.9	18.4	20.2	16.4	17.9	19.7
<b>3.00</b>	20.6	17.0	12.7	17.1	18.6	20.4	16.5	18.0	19.8

Predicted Build Rate figures are in %/100' and are theoretical calculations of a non-flexible motor.